



global solutions :
local support™

NLOS Series Horizontally Polarized Omni 900 to 928 MHz Operation

The NLOS series horizontally polarized omnidirectional antenna systems offered by Laird Technologies are constructed of a heavy duty aluminum extrusion and then powder coat painted for extremely long service life. The super heavy duty mounting system will insure a stable installation in high wind conditions. The antennas are horizontally polarized so that interference can be minimized in the wireless system.

Features and Benefits:

- 900MHz omni directional antenna
- 9dBi gain
- Heavy duty aluminum extrusion with powder coat paint
- Type N female integrated connector standard

Applications

- 900 MHz ISM band applications
- WISP base station equipment
- Non line of sight applications
- Point to multi-point systems

For sales information:

Telephone 800-323-3757

E-Mail sales@pacwireless.com

or visit: www.pacwireless.com

Specifications

Parameter	Min	Typ	Max	Units
Frequency Range	900		928	MHz
Gain		9		dBi
Vertical Beamwidth		18		Deg
Horizontal Beamwidth		360		Deg
Cross Polarization Rej		-22		dB
VSWR		1.5:1		
Impedance		50		OHM
Input Power			100	W
Pole Diameter (OD)	1.5 (38)		3 (76)	Inch (mm)
Operating Temperature	-45		+70	Deg C
Weight		22 (10)		Lbs (kg)
Length x Width x Depth	62" x 8" x 2" (1575 x 203 x 51)			Inch (mm)

Model	Sq. In	100MPH	125MPH
ODH9-9	496	124 Lbs	194 Lbs

System Ordering:

ODH9-9 9dBi 900MHz horizontally polarized omnidirectional antenna


Notes:

- All shipments F.O.B. Schaumburg, IL 60173
- All antennas carry a 2 Year Warranty

Any information furnished by Laird Technologies and its agents is believed to be accurate and reliable. Responsibility for the use and application of Laird Technologies materials rests with the end user since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability, or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies domestic terms and conditions of sale in effect from time to time, a copy of which will be furnished upon request.

Specifications subject to change without notice.

Antenna Patterns at 928MHz



ODH9-9 Mount

